



## SPECIFICATIONS

### **Failsafe 10/100/1000Base-T Network Tap**

(Model No. ETAP-3105)

|  |  |
|--|--|
| Model No.                                  | ETAP-3105  |
| Inline Link Interface                      | RJ45, 10/100/1000Base-T                                    |
| Cable Requirements                         | UTP CAT5e up to 328ft/100m                                 |
| Number of Aggregation Monitoring Ports     | 1  |
| Number of Non-Aggregation Monitoring Ports | 2  |
| Failsafe By-Pass                           | Yes  |
| Link Fault Pass-Through                    | Yes  |
| PoE Compatibility                          | Yes. Supports 802.3af (PoE) and 802.3at (PoE+)             |
| Compatibility with VLAN Tagged Packets     | Yes  |
| Jumbo Frame                                | 10KBytes   |
| LED Indicators                             | 1x power LED<br>1x Link/Activity LED for each network port |
| Power Supply Input                         | 5V DC  |
| Power Consumption                          | < 5W   |
| Operating Temperature Range                | 0°C to 40°C  |
| Number of Cooling Fans                     | Zero. Fan-less   |
| Dimensions                                 | 6.9"x 4.9" x 1.2" (L x W x H)                              |
| ROHS Compliance                            | Yes  |
| EMC Compliances                            | FCC Part 15 and CE   |
| Warranty                                   | One year manufacturer warranty                             |